



Rowa Vmax™ 130

Technical data

Dimensions	Width	1.33 m	
	Height	2.10–3.50 m (in 5 cm intervals)	
	Length	2.68–15.17 m (in 48 cm intervals)	
Sound level	The average sound pressure level $L_{p,m}$ is 48.3 dB (A)		
Possible locations	Ground floor, basement, upper floor		
Input and output times	Input	Approx. 3 seconds (Direct availability for over-the-counter sales)	
	Output	Approx. 8 – 12 seconds (several packages at the same time possible)	
Storable package sizes	Square packages		
	Min. package size (D x W x H)	35 x 15 x 15 mm	
	Max. package size (D x W x H)	230 x 140 x 145 mm	
	Weight	5–1,000 g	
	Round packages		
	Min. package size	Ø 45 mm, height: 15 mm	
	Max. package size	Ø 140 mm, height: 145 mm	
	Weight	5–800 g	
Barcodes	Identification and reading of PZN, PZN8, EAN, and 2D barcodes		
Electrical Parameter	8 A, 230 V, 50/60 Hz		
Power consumption	In operation	650 W with one picking head	
		780 W with two picking heads	
	In standby mode	348 W with one picking head	
		379 W with two picking heads	
Safety	System protection thanks to uninterrupted power supply (UPS), backup computer, remote monitoring		
Options	2 nd picking head	2 nd Input belt	Rowa Label™ (labeling)
	Rowa cleaning module	Rowa System backup	Rowa ProLog™ external (fully automatic input)
	Rowa refrigerated unit		
Conveyor technology	Conveyor belt, servo controlled lift, spiral chute with Ø 400 mm, possible to connect up pneumatic tube transport		
Colors	White (RAL 9016), anthracite (RAL Design 000-25-00)		

Becton Dickinson Rowa Germany GmbH, RowastraÙe, D-53539 Kelberg
+49 2692 92 06 0 tel, +49 2692 92 06 1299 fax

bd.com/rowa

