



Rowa Vmax[®] 210

Technical data

Dimensions	Width	2.13 m	
	Height	2.10 m–3.50 m <i>(in 5-cm increments)</i>	
	Length	3.20 m– 15.04 m <i>(in 32-cm increments)</i>	
Sound level	Average sound pressure level LpA,m	50.9 dB(A)	
Possible locations	Ground floor, basement, upper floor		
Input and output times	Input	Approx. 3 seconds <i>(Direct availability for over-the-counter sales)</i>	
	Output	Approx. 8 – 12 seconds	
Storable pack sizes*	Square packages	Min. package size (L × W × H)	35 × 15 × 15 mm
		Max. package size (L × W × H)	500 × 250 × 150 mm
		Weight	5–1,000 g
Barcodes	Identification and reading of PZN, PZN8, EAN, and 2D barcodes		
Electrical Parameter	8 A, 230 V, 50/60 Hz 16 A, 120 V, 50/60 Hz		
Safety	System protection thanks to uninterrupted power supply (UPS), backup computer, remote monitoring		
Options	2 nd Input belt		
	Rowa ProLog [®] external <i>(fully automatic input)</i>		
Conveyor technology	Conveyor belt, servo-controlled lift, spiral chute with Ø 400 mm, possible to connect up pneumatic tube transport		
Colors	White (RAL 9016), anthracite (RAL Design 000-25-00)		

* The information provided is preliminary and could be subject to change.

Large packs (from D: 230 × W: 145 × H: 140 mm) cannot be removed via connected conveyor technology.

These packs can only be removed directly from storage at the Rowa storage area.

Becton Dickinson Rowa Germany GmbH, RowastraÙe, D-53539 Kelberg
+49 2692 92 06 0 tel, +49 2692 92 06 1299 fax

bd.com/rowa

