



# Rowa™ conveyor systems

Extremely short routes

## Technical data

Conveyor belt	Belt width	321 mm
	Nominal width between sides	285 mm
	Total width at the side with motor	397.5 mm
	Length	500–10,000 mm
	Height	217 mm (without Motor) / 287 mm (with Motor)
	Speed	Variable up to 1.8 m/s
	Sound level	54,5 dB (A) (with a belt length of 10,000 mm and with a speed of 1.2 m/s)
	Weight	Approx. 50 kg (with a length of 2,000 mm; for each additional meter: approx. 15 kg)
	Power requirement	max. 400 W
Wiper	Dimensions (H × L)	130 × 510 mm
	Size of wiper housing (L × W × H)	203 × 100 × 209 mm
	Opening angle	45°
	Weight	7 kg

Chute	Width inside	285 mm
	Width outside	297 mm
	Length	425 mm / 925 mm / 1,925 mm
	Tilt angle	20° – 45°
	Weight	Approx. 7 kg with a length of 1.925 mm
	Material	Polystyrol
	Conveyable Packages ( <i>D × W × H</i> )	Max. 230 × 140 × 100 mm*
Spiral chute	Diameter	400 mm
	Flexure	90° per segment
	Vertical Height	150 mm per segment
	Weight	0.5 kg per segment
	Material	Polyamid
	Conveyable Packages ( <i>D × W × H</i> )	Max. 230 × 140 × 100 mm*
Lift	Conveyor height	Standard up to 8,400 mm ( <i>up to 14,700 mm on request</i> )
	Outer dimensions ( <i>W × L</i> )	258 mm × 299 mm
	Weight	Approx. 34 kg for a lift with a length of 2,760 mm
		Approx. 6.5 kg for each additional meter
	Power requirement	500 W
	Material	Covering made of plastics
	Conveyable Packages ( <i>D × W × H</i> )	Max. 230 × 140 × 100 mm*

\* Larger packages can also be transported (*max. 500 × 250 × 145 mm [D × W × H] and 800 g*).

The chute must be straight, the conveyor belt at least 1 m long and only connected to other components at the end of the unit.



Becton Dickinson Rowa Germany GmbH, Rowastraße, D-53539 Kelberg  
 +49 2692 92 06 0 tel, +49 2692 92 06 1299 fax

[bd.com/rowa](http://bd.com/rowa)

